



Ground Cover Industries, Inc.

CHOICE 200 – 200# TENSILE STRENGTH WOVEN FABRIC

Choice 200 – 200# Tensile Strength Heavy Duty Woven Construction Fabric – is a woven geotextile manufactured using polypropylene yarns. Choice 200 resists ultraviolet deterioration, rotting, biological degradation, and is inert to commonly encountered soil chemicals. Choice 200 is useful for soil stabilization applications.

Property	Test Method	Unit	Minimum Average Roll Value
Grab Tensile	ASTM D4632	LBS	200
Grab Elongation	ASTM D4632	%	15
Trapezoid Tear Strength	ASTM D4533	LBS	75
CBR Puncture Resistance	ASTM D6241	LBS	700
Permittivity	ASTM D4491	Sec ¹	0.05
Water Flow	ASTM D4491	GPM/FT ²	5
AOS	ASTM D4751	US SIEVE	40
UV Resistance	ASTM D4355	%/HRS	70/500

PROPERTY

Roll Sizes

TYPICAL

12.5'x432'

15'x360'

Date: 4/21/17

Disclaimer: Ground Cover Industries, Inc. assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. Ground Cover Industries, Inc. disclaims any and all implied, expressed, or statutory standards, guarantees, or warranties. This includes without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Always consult the project engineer for project specifics. The end user assumes sole responsibility for the use of this information and product.

The property values listed above are subject to change without notice. 2015 Ground Cover Industries, Inc.

GROUND COVER INDUSTRIES, INC.
PO Box 1933 - Santa Rosa Beach, FL 32459
817-633-4020 / 817-633-4023 fax

