



# Ground Cover Industries, Inc.

## SPECIFICATION DATA

### 320 Series - NURSERYMEN'S CHOICE

**320 Series - NURSERYMEN'S CHOICE** is manufactured using high tenacity polypropylene yarns that are woven to form a dimensionally stable network, which allows the yarns to maintain their relative position. The woven fabric conserves soil moisture and is effective for weed suppression in a nursery environment.

**320 Series - NURSERYMEN'S CHOICE** resists ultraviolet deterioration, rotting, and biological degradation and is inert to commonly encountered soil chemicals.

PROPERTY	TEST METHOD	TYPICAL
Fabric Color		Black
Stripe Color (every 12")		Green
Weight	ASTM D-3776	3.1 oz/sy
Thickness	ASTM D-1777	15 mls
Tensile Strength	ASTM D-4632	175 x 115 lbs
Elongation	ASTM D-4632	24 x 20%
Puncture	ASTM D-4833	550 lbs
Trapezoidal Tear	ASTM D-4533	75 x 60 lbs
UV Resistance (2,500 hours)	ASTM D-4355	70%
Apparent Opening Size (AOS)	ASTM D-4751	40 US Std Sieve
Water Flow Rate	ASTM D-4491	6 gpm/sf

\*Maximum Average Roll Value

PROPERTY	TYPICAL
Roll Sizes	3' x 300'
	4' x 300'
	6' x 300'
	10' x 300'
	12' x 300'
	15' x 300'

**Disclaimer:** Ground Cover Industries, Inc. assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. Ground Cover Industries, Inc. disclaims any and all implied, expressed, or statutory standards, guarantees, or warranties. This includes without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Always consult the project engineer for project specifics. The end user assumes sole responsibility for the use of this information and product.

The property values listed above are subject to change without notice. 2015 Ground Cover Industries, Inc.

**GROUND COVER INDUSTRIES, INC.**  
**PO Box 1933 - Santa Rosa Beach, FL 32459**  
**817-633-4020 / 817-633-4023 fax**

