



Ground Cover Industries, Inc.

SPECIFICATION DATA

600 Series - PROFESSIONAL'S CHOICE

600 Series - PROFESSIONAL'S CHOICE is nonwoven geotextile that is needle-punched and made of 100% polypropylene fibers, which are formed into a random network for dimensional stability. ALL GCI Non-Woven Fabrics resist ultra-violet deterioration, rotting, and biological degradation. Polypropylene is stable within a pH range of 2 to 13

PROPERTY	TEST METHOD	TYPICAL
Fabric Color		Black
Weight	ASTM D-5261	6 oz/sy
Tensile Strength(lbs)	ASTM D-4632	160
Elongation %	ASTM D-4632	0.5
Puncture (lbs)	ASTM D-6241	410
Trapezoidal Tear	ASTM D-4533	65
UV Resistance (%/hours)	ASTM D-4355	70/500
Apparent Opening Size (AOS)	ASTM D-4751	70
Water Flow Rate	ASTM D-4491	110 gpm/sf

*Maximum Average Roll Value

PROPERTY	TYPICAL
Roll Sizes	3' x 250'
	4' x 250'
	5' x 250'
	6' x 250'
	7.5' x 250'
	10' x 250'
	12' x 250'
	15' x 250'

Disclaimer: Ground Cover Industries, Inc. assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. Ground Cover Industries, Inc. disclaims any and all implied, expressed, or statutory standards, guarantees, or warranties. This includes without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Always consult the project engineer for project specifics. The end user assumes sole responsibility for the use of this information and product.

The property values listed above are subject to change without notice. 2015 Ground Cover Industries, Inc.

GROUND COVER INDUSTRIES, INC.
PO Box 1933 - Santa Rosa Beach, FL 32459
817-633-4020 / 817-633-4023 fax

