



# Ground Cover Industries, Inc.

## CHOICE 315 – 315# TENSILE STRENGTH WOVEN FABRIC

**Choice 315 – 315# Tensile Strength Heavy Duty Woven Construction Fabric** – is a woven geotextile manufactured using polypropylene yarns. Choice 315 resists ultraviolet deterioration, rotting, biological degradation, and is inert to commonly encountered soil chemicals.

<b>Property</b>	<b>Test Method</b>	<b>Unit</b>	<b>Minimum Average Roll Value</b>
Grab Tensile	ASTM D4632	LBS	315
Grab Elongation	ASTM D4632	%	15
Trapezoid Tear Strength	ASTM D4533	LBS	120
CBR Puncture Resistance	ASTM D6241	LBS	1000
Permittivity	ASTM D4491	Sec <sup>1</sup>	0.05
Water Flow	ASTM D4491	GPM/FT <sup>2</sup>	4
AOS	ASTM D4751	US SIEVE	40
UV Resistance	ASTM D4355	%/HRS	70/500

### PROPERTY

Roll Sizes

### TYPICAL

12.5'x360'

15'x300'

Date: 4/21/17

**Disclaimer:** Ground Cover Industries, Inc. assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. Ground Cover Industries, Inc. disclaims any and all implied, expressed, or statutory standards, guarantees, or warranties. This includes without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Always consult the project engineer for project specifics. The end user assumes sole responsibility for the use of this information and product.

The property values listed above are subject to change without notice. 2015 Ground Cover Industries, Inc.

**GROUND COVER INDUSTRIES, INC.**  
**PO Box 1933 - Santa Rosa Beach, FL 32459**  
**817-633-4020 / 817-633-4023 fax**

